

Cables

Description

RST Instruments Ltd. offers a variety of cables that can be effectively matched to any instrument that requires a signal cable. RST uses Meter Marked Cable for a majority of our instruments that require a signal cable such as those used in Vibrating Wire Piezometers, Load/Pressure Cells, Crack Meters, Joint Meters, etc. In the unfortunate event of the cable being accidentally severed, the meter cable markings can be cross-referenced with the calibration record.

CABLE SPECIFICATIONS

MODEL	DESCRIPTION	USED FOR:	CONDUCTORS	DIAM. O.D.
EL380002	Abrasion-resistant polyurethane jacket.	Single Point Thermistors	2 (1 twisted pair), 24 AWG (0.20 mm ²)	5.33 mm (0.210 in.)
EL380004	Standard vibrating wire cable, abrasion-resistant polyurethane jacket.	• Vibrating Wire Piezometers and most other VW instruments • Strain Gauge Load Cells • MEMS In-place Inclinometers • MEMS Tilt Meters & Beams Direct burial of surface cable for: • Vibrating Wire Piezometers and most other VW instruments • MEMS In-place Inclinometers • MEMS Tilt Meters & Beams	4 (2 twisted pairs), 22 AWG (0.33 mm ²)	6.35 mm (0.250 in.)
EL380004HDL	Heavy Duty Cable with a thick polyurethane jacket mold for added protection.	• Vibrating Wire Piezometers and most other VW instruments • MEMS In-place Inclinometers • MEMS Tilt Meters & Beams	4 (2 twisted pairs), 22 AWG (0.33 mm ²)	9.52 mm (0.375 in.)

EL380004K	Kevlar® reinforced, non-stretch polyurethane jacketed cable for rigorous installations where the stretching of the cable is a concern.	VW Piezometers	4 (2 twisted pairs), 22 AWG (0.33 mm ²)	6.35 mm (0.250 in.)
EL370004	Thin polyurethane jacket mold.	<ul style="list-style-type: none"> • VW Rebar Strain Meters • VW Embedment Strain Gauges • VW Arc Weldable Strain Gauges • Used in acidic applications (leachate) and landfills • Saltwater 	4 (2 twisted pairs), 24 AWG (0.20 mm ²)	4.76 mm (0.1875 in.)
EL342202	HDPE jacket.	<ul style="list-style-type: none"> • Used in acidic applications (leachate) and landfills • Saltwater 	4 (2 twisted pairs), 22 AWG (0.33 mm ²)	6.35 mm (0.250 in.)
EL35VT04	Vented polyurethane cable for barometric compensation; Kevlar® reinforced.	Low-Pressure Vented Transducers	4 (2 twisted pairs), 22 AWG (0.33 mm ²)	7.92 mm (0.312 in.) (jacket) 3.17 mm (0.125 in.) OD (vent tube)
EL380006	Water blocked, polyurethane jacket. Grease blocked.	<ul style="list-style-type: none"> • In-Place Tiltmeters (analog biaxial) • Strain Gauge Analog Piezometer with Thermistor • Push-In Pressure Cells • Thermistor Strings • MPBX Heads • VW Load Cells • Remote multiplexer connection cable to logger • Thermistor Strings • Thermistor Strings and VW Piezometer Strings • VW Load Cells • MPBX Heads 	6 (3 twisted pairs), 22 AWG (0.33 mm ²)	6.35 mm (0.250 in.)
EL360008	Polyurethane jacket.	<ul style="list-style-type: none"> • MPBX Heads • VW Load Cells • Remote multiplexer connection cable to logger • Thermistor Strings • Thermistor Strings and VW Piezometer Strings • VW Load Cells • MPBX Heads 	8 (4 twisted pairs), 20 AWG (0.52 mm ²)	8.13 mm (0.320 in.)
EL380012	Kevlar® reinforced, polyurethane jacket. Grease blocked.	<ul style="list-style-type: none"> • Thermistor Strings and VW Piezometer Strings • VW Load Cells • MPBX Heads 	12 (6 twisted pairs), 24 AWG (0.20 mm ²)	10.54 mm (0.415 in.)

EL380007P	Polyurethane jacket. Kevlar® reinforced, polyurethane jacket. Grease blocked.	• Thermistor Strings and VW Piezometer Strings • VW Load Cells • MPBX Heads • Thermistor Strings and VW Piezometer Strings • VW Load Cells • MPBX Heads	14 conductors (7 pairs), 22 AWG (0.33 mm ²) 26 (13 twisted pairs), 24 AWG (0.20 mm ²)	9.84 mm (0.3875in.) 10.88 mm (0.425 in.)
-----------	---	--	--	--

SPECIFICATIONS