

## Casagrande Standpipe Piezometer

### Description

**NOTE: This is a legacy and discontinued product not available for order.**

RST's Casagrande Standpipe Piezometer tip consists of a slotted PVC body that encloses and protects a porous plastic filter element. A PVC Riser Pipe (available from RST) is connected to the tip and extended to the surface. A CPVC body is available for leachate extraction. The Casagrande Standpipe Piezometer is mainly used for measurement of piezometric levels and pore water pressures in soil and rock formations where the time lag and high displacement requirements inherent in standpipes are not crucial, and where the presence of standpipes will not hinder construction. Water elevation in the riser pipe is measured using a Water Level Meter. Alternatively, a Vibrating Wire Piezometer can be lowered in the pipe to allow remote reading.

### CASAGRANDE STANDPIPE PIEZOMETER SPECIFICATIONS

ITEM	SPECIFICATION
Pore Diameter	70 micron
Permeability	$3 \times 10^{-4}$ m/s (low air entry)
Maximum O.D.	1.32 in. (3.35 cm)
Minimum I.D.	0.63 in. (1.6 cm)
Filter Area	37.69 sq. in. (243 sq. cm)
Body Material	1 in. PVC
Accepts 1 in., 0.75 in. and 0.5 in. PVC solvent weld riser pipe.	
SPECIFICATIONS	