## DT2350: Load Cell Data Logger

## **Description**

## NOTE: This is a legacy and discontinued product not available for order.

The DT2350 Load Cell Data Logger is a 2 channel data logger for resistance strain gauge load cells and other strain gauge sensors, pressure transducers, etc. The DT2350 is part of RST's "DT Series" Data Loggers and is fully compatible with the RSTAR or DT LINK Wireless Data Collection Systems.

## DT2350: Load Cell Data Logger Specifications

ITEM	SPECIFICATION

Analog Channels 2

Analog Sensors Supported Bridge Transducers
Thermistor A/D Type 24 Bit Delta-Sigma
0.001%

Zero Stability (Logger Only)

Nonlinearity (Logger Only)

0.003%

AMP Floor

Memory Type 4MB Flash
Memory Records Up to 600,0

Memory Records Up to 600,000 records of Date/Time, 2 Sensors Memory Endurance Unpowered 100 years

Power Source Lithium compact or standard cell battery (NOTE:

standard cell required for radio use)

Up to 4 years (non-radio or RSTAR) or 3.5 years (DT

Battery Life LINK) (NOTE: specs based on 1-hour reading frequency and dependent on temperature and use)

Enclosure NEMA 4X (IP65)

Dimensions 120 x 122 x 90 mm (4.72 x. 4.80 x 3.54 in.)

Specifications