

MR3003DMS

Description

The MR3003DMS seismic monitoring system is the most compact, integrated and reliable system for dams, ensuring the highest level of safety and sustainability. Automatic earthquake detection and structural monitoring will ensure the dam full integrity over its lifetime.

The MR3003DMS is extremely versatile and easy to install, thanks to its state of the art Ethernet master-slave connectivity and the command & control access through embedded web server.

3 relays output (alarm 1, alarm 2, device error) can be directly connected to the control room for a centralized overview and an automatic logic response in case of any seismic event.

Data acquisition

ITEM

General Principle

Resolution

Sampling-rate

Number of channels

Channel to channel skew

Dynamic range

Data Filter

Trigger Filter

SPECIFICATION

4th order delta-sigma ADC per channel

24 bits

250, 500, 1000, 2000, 4000 sps

3

None, simultaneous sampling on all channels

Typ. 130dB@250 sps, 124dB@1000 sps

Anti-aliasing filters

Digital IIR filter: 0.5 to 15 Hz band-pass (Strong Motion Applications)

Trigger and de-trigger

ITEM

Principle

Trigger voting logic

Trigger level

STA / LTA

Smart Trigger / De-Trigger

SPECIFICATION

Level trigger or STA/LTA or automatic adjustment of trigger level

Predefined AND or OR combinations, individual channel votes

0.1 mg to 4 g

STA: 0.1 to 25s, LTA: 1 to 250s, ratio 0.1:25

Automatic adjustment of trigger level

Microprocessor

Recording Principle	Event recording (time history), continuous-time recording, or manually triggered
Header	Contains status information at time of trigger and event summary
Pre-event recording	1-99 seconds (@250Hz), others depending on sampling rate
Post-event recording	1-100 seconds
Max. recording time	Unlimited
Memory Removable	SD flash card (4GB)
Timing System clock	1ppm, could be disciplined by GPS or NTP
Data / User Interface Web interface	Easy to use command & control through embedded web server
Intelligent Alerting	System initiates communications and sends e-mail when an event is recorded
FTP Built-in	Built-in client protocol supporting FTP, SFTP, FTPS able to push to a server
Alarm triggers Principle	Two alarm levels independently settable as threshold levels or user-defined
Alarm level range	0.1 % to 100% full scale
User-defined alarm	Thresholds and frequencies individually settable for each axis
System status	3 LEDs Run, Recording, Warning/Error. Internal LCD with status info and important settings

Network capabilities

ITEM

Common trigger and common alarm
Sync. in LAN network
Max. number of MR3003DMS
Remote control

SPECIFICATION

Configurable with AND/OR logic, for every device within the same network
Typically 1 ms with NTP protocol
32, in Master/slave configuration
VPN, DDNS

Power Supply

ITEM

Power supply
Internal battery
Consumption
Battery autonomy

SPECIFICATION

100 - 240 V AC, 50 - 60 Hz, OVP protected, type I and II. Optional DC power 10-36 V DC
12 V, 12 Ah
4 W (with charged battery), 25 W (AC max. and battery in charge)
Typ. 40 hours

I/O (glands and connectors)

ITEM

Relays (3)

Power

Kit LAN

Kit GPS

FO

SPECIFICATION

M16 cable gland 7-11mm / Terminals

M16 cable gland 4-11mm / Terminals

On request, 3 m Ethernet cable

On request, connector and GPS antenna with 5 m cable for time synchronization

M20 cable gland 6-13 mm / ST connectors

Fiber Optics

ITEM

FO type

SPECIFICATION

Multimode OM2 fiber with wavelength 1300 nm, 50/125 $\hat{1}$ /₄m, Rx/Tx

Relays

ITEM

Configuration

Current

SPECIFICATION

3 output configurable relays, No/Nc

2 A, 30 V DC

Acceleration sensor

ITEM

Principle

Hysteresis

Noise (10 to 1000 Hz)

Frequency range

Dynamic range

Measuring range

Sensitivity

Scale factor error

Orientation

Self test

SPECIFICATION

Micro-machined capacity MEMS accelerometer

None

Typ. 7 $\hat{1}$ /₄g/ \hat{a} ?? Hz

DC to 600 Hz

Typ. 100 dB @ 200 sps

\hat{A} \pm 4 g

1.25 V/g differential

< 1 %

Horizontal or vertical mounting, to be specified when ordering

Test-pulse, configurable

Housing

ITEM

Dimensions
Weight
Protection degree

SPECIFICATION

330 x 230 x 110 mm
10 Kg
IP66

Environmental**ITEM**

Shock
Heat
Humidity

SPECIFICATION

30 g/11 ms half-sine
-20 °C to +50°C
up to 100% RH

Regulations**ITEM**

EMC
Electrical safety
Conformity
Origin
Specifications

SPECIFICATION

IEC 61326-1
IEC 61010
CE
Swiss Made