

## PVC Wellscreen and Threaded Pipe

### Description

**NOTE: This is a legacy and discontinued product not available for order.**

RST Accu-Seal PVC Wellscreen and Pipe is a system of top-quality monitoring pipe products for groundwater hydrology, environmental, drainage, water wells, and geotechnical applications. The pipe can be slotted and/or threaded.

RST's Flush Threaded PVC Well Casing is engineered to be assembled quickly and accurately for use in water wells and similar applications. Slotted PVC Well Screens are also available.

### PVC WELLSCREEN AND THREADED PIPE SPECIFICATIONS: SCHEDULE 40

INCHES	LENGTHS (NOMINAL)	O.D.	I.D.	THREAD OPTION	SLOTS (FULL LENGTH, STANDARD PATTERN)
1.0	5 ft., 10 ft.	1.315	1.049	F480	0.010 in., 0.020 in.
1.5	5 ft., 10 ft.	1.900	1.610	F480	0.010 in., 0.020 in.
2.0	5 ft., 10 ft.	2.375	2.067	F480	0.010 in., 0.020 in.
2.5	5 ft., 10 ft.	2.875	2.469	F480	0.010 in., 0.020 in.

### PVC WELLSCREEN AND THREADED PIPE SPECIFICATIONS: SCHEDULE 80

INCHES	LENGTHS (NOMINAL)	O.D.	I.D.	THREAD OPTION	SLOTS (FULL LENGTH, STANDARD PATTERN)
0.75	5 ft., 10 ft.	1.050	0.741	F480	N/A
1.0	5 ft., 10 ft.	1.315	0.957	F480	0.010 in., 0.020 in.
1.5	5 ft., 10 ft.	1.900	1.500	F480	0.010 in., 0.020 in.
2.0	5 ft., 10 ft.	2.375	1.939	F480	0.010 in., 0.020 in.
2.5	5 ft., 10 ft.	2.875	2.323	F480	0.010 in., 0.020 in.

---

## SPECIFICATIONS