

PVC Wellscreen and Threaded Pipe

Description

NOTE: This is a legacy and discontinued product not available for order.

RST Accu-Seal PVC Wellscreen and Pipe is a system of top-quality monitoring pipe products for groundwater hydrology, environmental, drainage, water wells, and geotechnical applications. The pipe can be slotted and/or threaded.

RST's Flush Threaded PVC Well Casing is engineered to be assembled quickly and accurately for use in water wells and similar applications. Slotted PVC Well Screens are also available.

PVC WELLSCREEN AND THREADED PIPE SPECIFICATIONS: SCHEDULE 40

INCHES	LENGTHS (NOMINAL)	O.D.	I.D.	THREAD OPTION	SLOTS (FULL LENGTH, STANDARD PATTERN)
1.0	5 ft., 10 ft.	1.315	1.049	F480	0.010 in., 0.020 in.
1.5	5 ft., 10 ft.	1.900	1.610	F480	0.010 in., 0.020 in.
2.0	5 ft., 10 ft.	2.375	2.067	F480	0.010 in., 0.020 in.
2.5	5 ft., 10 ft.	2.875	2.469	F480	0.010 in., 0.020 in.

PVC WELLSCREEN AND THREADED PIPE SPECIFICATIONS: SCHEDULE 80

INCHES	LENGTHS (NOMINAL)	O.D.	I.D.	THREAD OPTION	SLOTS (FULL LENGTH, STANDARD PATTERN)
0.75	5 ft., 10 ft.	1.050	0.741	F480	N/A
1.0	5 ft., 10 ft.	1.315	0.957	F480	0.010 in., 0.020 in.
1.5	5 ft., 10 ft.	1.900	1.500	F480	0.010 in., 0.020 in.
2.0	5 ft., 10 ft.	2.375	1.939	F480	0.010 in., 0.020 in.
2.5	5 ft., 10 ft.	2.875	2.323	F480	0.010 in., 0.020 in.

SPECIFICATIONS