

VW2106: Vibrating Wire Readout

Description

The portable VW2106 Vibrating Wire Readout reads, displays, and logs both vibrating wire sensors and thermistors. Vibrating wire load cells can be read without any additional accessories.

Unprecedented accuracy, flexible memory options and ease of use make the VW2106 invaluable for projects requiring vibrating wire sensor monitoring. Maximum download time is only 15 seconds.

VW2106: Vibrating Wire Readout Specifications

ITEM	SPECIFICATION
Vibrating Wire Readout Excitation Range	400 Hz to 6000 Hz, 5 V Square Wave
Vibrating Wire Readout Resolution	0.01 μ s
Vibrating Wire Readout Timebase Accuracy	\pm 50 ppm
Supported Temperature Readout Sensors	NTC3000 (standard), NTC2252, NTC10K, RTD
Temperature Readout Accuracy	\pm 0.1°C
Temperature Readout Range	-50°C to 80°C
Display	Graphic 128 x 64 pixels large character display
Display Backlight	High efficiency LCD with auto off
Max Instrument Locations	254
Memory Capacity	11,400 custom labelled points
Location Identification String	Up to 20 characters
Download Speed	15 seconds (full memory)
Battery	3 "AA" alkaline
Battery Indicator	On-screen, low battery indicator
Operating Temperature	-20°C to 60°C
Dimensions	W 22 cm x D 19 cm x H 9.5 cm (8.75 x 7.5 x 3.75in.)
Weight	1.1 kg (2.4 lbs)

SPECIFICATIONS