







PRODUCT CATEGORY: ENVIRONMENTAL

Water Level Meters

RST Water Level Meters are used for convenient and accurate measurement of elevation of groundwater in boreholes, standpipes, and wells. They employ a high accuracy, NIST traceable, non-stretch, flat tape, permanently marked in 1 mm or 1/100 ft. graduations.

The RST Water Level Meter is supplied on a sturdy winding reel complete with a brake and carrying handle. Features include a shrouded stainless steel probe (allows accurate level determinations under cascading water conditions), a buzzer (with adjustable volume control), and sensitivity control as standard. The moisture resistant electronics and standard 9V battery are housed in the front for quick and easy access.

> APPLICATIONS

Measuring the elevation of groundwater in standpipes, boreholes, and wells.

> FEATURES

An ultra-wide user defined conductivity range allows for use in different liquids ranging from pure water to neat cement grout.	Frontal battery (standard 9 V) compartment needs no tools for removal/battery replacement.
Auto buzzer check at start up.	Auto OFF
Multi-functional button and knob act as the control interface.	Rugged design for the most adverse conditions.
Sensitivity adjustment.	Tape markings will not fade or wear away.
NIST traceable, non-stretch steel tape, polyethylene coated.	Resolution: 1 mm or 1/100 ft. Accuracy: 0.1%
7 strand, 24 gauge stainless steel conductors.	13 mm / 0.5 in. O.D. stainless steel probe.

Sensing point at bottom of probe causes negligible water displacement ensuring high accuracy readings.

> BENEFITS

✓ High Reliability

√ High Accuracy

SPECIFICATIONS

TAPE LENGTH *CONTACT RST FOR ADDITIONAL LENGTHS*	PART#
	POLY TAPE
30 m	WL1030
50 m	WL1050
100 m	WL1100
150 m*	WL1150
200 m*	WL1200
300 m**	WL1300
100 ft	WL2010
150 ft	WL2015
300 ft	WL2030
500 ft*	WL2050
	•

* Mounted on a medium sized reel.

** Mounted on a large sized reel.

ACCESSORIES

ITEM	PART#
Aluminum carrying/shipping cases: - up to 100 m / 300 ft - 150-200 m / 500 ft - 300 m	WL6505 WL6504 IC3031C
Soft vinyl carrying cases: - up to 200 m / 500 ft - 300 m	WL6506 IC6508
Replacement tapes with probe	Please contact RST for more information.



Contact RST for Details